



LED ENHANCED SIGNS

- Enhance Visibility
- Improve Driver Response

OVERVIEW

LED ENHANCED SIGNS

REGULATORY, STANDARD & CUSTOMIZED SIGNS



SN-LED-R11



SN-LED-R11



CUSTOMIZED



SN-LED-W112



SN-LED-S11



SN-LED-W11-8



SN-LED-W112



SN-LED-W12



SN-LED-PS8



Roundabout LED Enhanced Signs

The 48 x 24 in. sign features three LED-enhanced arrows; each arrow has ten white LED flashers. During the lighting chase sequence, each arrow is illuminated separately, and progression follows the direction of the arrows and repeats until the configured activation time expires. Separate signs operate independently of each other.

The LaneLight control cabinet designed specifically for this sign contains a power converter, an LED Sequencer, and a radar sensor unit. The radar sensor, mounted inside the control cabinet door, detects the presence of oncoming traffic and sends an activation signal to the LED Sequencer, which activates the LEDs on the sign.



SPECIFICATIONS

Power	Solar or AC Options
Operation	Pedestrian Activated / 24-7 / 365 Day Scheduler
Connection	Wired or RF Wireless Options
Operating Voltage	10-30 VDC

Signs

Dimensions	Standard MUTCD or Custom
Reflectivity	Diamond Grade with Anti-Graffiti overlay
Substrate	.080 Highway Grade Aluminum

LEDs

LED Size	1 in. [25mm]
LED Quantity	Depends on the sign shape
LED Colour	Yellow, Red or White depending on sign type
Flash Pattern	Pulsed, MUTCD Compliant