



## SCHOOL ZONE FLASHING BEACON

# Programmable LED enhanced signage

(in)

f


www.lanelight.com



### **OVERVIEW**

Monitor and control LaneLight devices remotely from a secure web site on any internet-enabled device.

## School Zone Flashing Beacon





#### OVERVIEW

A single or dual Beacon with Top of Pole Solar Control Cabinet installs easily onto any new or existing sign post and provides effective notification to drivers. The system can be configured to run trough a range of time or utilize an optional vehicle detection radar sensor to activate the system.

| SPECIFICATIONS              |  |
|-----------------------------|--|
| Beacon Assembly             |  |
| Beacon Size Options         | 8 in. or 12 in.  |
| LED Color                   | Red or Amber   |
| Flash Pattern               | MUTCD compliant Wig-Wag  |
| Beacon Certification        | Protection Class: Safety Class II  |
|                             | Impact Resistance: Class IR3   |
|                             | Protection: IP 65  |
| Beacon Housing              |  |
| Material                    | UV-stabilized polycarbonate  |
| Color Options               | All black, all yellow, yellow body with black front panel  |
| Mounting Hardware           | Aluminum, powder coated  |
| Mounting Options            | Side-of-pole: Hub plate mount, bolts or metal banding  |
| Top of Pole Solar Contro    | I Cabinet  |
| Material                    | 0.125 in. 5052 Aluminum  |
| Dimensions                  | 21 in. x 13.80 in. x 5.4 in.   |
| Construction                | Welded box construction with gasket Top-mounted lid with piano hinge   |
| Hardware                    | Butterfly latch, spring lid support  |
| Mounting Options            | Top of pole mount adapter (max. pole 0 4.5 in.) Telespar adapter (1.5-   |
|                             | 2.5 in.), #1-1/2 in. nut Custom arm extension for side of pole mount   |
| Weight                      | 10 lb (with 20Ah battery)  |
| Power and Control           | 20W solar panel (mounted on lid) LaneLight SF 2 sign flasher   |
|                             | 3.6V/20Ah LiFePO4 battery"   |
| Autonomy                    | >20days  |
| Max. Wind Load              | Rated for wind speeds up to 170 mph (274 km/h)   |
| Standards Compliance        | Manufactured to NEMA 3R specifications   |
| **Optional aluminum side of | of pole cabinet  |
| Sign                        |  |
| Sign Size (s)               | 30 in. x 60 in. or 36 in. x 72 in.   |
| Sign Substrate              | 0.080 Highway Grade Aluminum   |
| Reflective Sheeting         | Diamond Grade with anti-graffiti overlay   |
| Color                       | As per MUTCD approved graphics   |
| Mounting                    | Bolt or band   |
| Warranty                    |  |
| Limited Warranty            | 5 year limited warranty for defects in manufacturing, factory assembly<br>and materials only; excludes damage caused by incorrect installation,<br>vehicles, or vandalism. |

16-755 Vanalman Ave, Victoria BC Canada V8Z 3B8

#### 1-866-466-4836 info@lanelight.com